


DATAsheet

7P/24V 125°C "Euro 6" coil (ISO 1185 - Type N)





Art.Nr.	611055
Part No.	011033

Industry Commercial vehicles No. of poles 7 Voltage [in V] 24 Standard ISO 1185 - Type N Special feature 125°C "Euro 6" version Packaging without packaging No. of connected plugs 2 No. of connected sockets 0 Housing material reinforced composite Housing color black Contact insert color black Cable outlet molded Mounting of cable and socket/plug molded Working length [in m] 3.0 Max. working length [in m] 4.5 Outer coil diameter [in mm] 50.0 Material of cable PUR Cable color black Wire cross-sectional area 6x 1.5mm² + 1x 2.5mm² Protection IP 44 Temperature resistance [in °C] -40.0 - 125.0 Product supplement Euro 6	Product group	Coil
Voltage [in V] 24 Standard ISO 1185 - Type N Special feature 125°C "Euro 6" version Packaging without packaging No. of connected plugs 2 No. of connected sockets 0 Housing material reinforced composite Housing color black Contact insert color black Cable outlet molded Mounting of cable and socket/plug molded Working length [in m] 3.0 Max. working length [in m] 4.0 Max. extension length [in m] 4.5 Outer coil diameter [in mm] 50.0 Material of cable PUR Cable color black Wire cross-sectional area 6x 1.5mm² + 1x 2.5mm² Protection IP 44 Temperature resistance [in °C] -40.0 - 125.0 Product supplement 125°C	Industry	Commercial vehicles
Standard ISO 1185 - Type N Special feature 125°C "Euro 6" version Packaging without packaging No. of connected plugs 2 No. of connected sockets 0 Housing material reinforced composite Housing color black Contact insert color black Cable outlet molded Mounting of cable and socket/plug molded Working length [in m] 3.0 Max. working length [in m] 4.0 Max. extension length [in m] 4.5 Outer coil diameter [in mm] 50.0 Material of cable PUR Cable color black Wire cross-sectional area 6x 1.5mm² + 1x 2.5mm² Protection IP 44 Temperature resistance [in °C] -40.0 - 125.0 Product supplement 125°C	No. of poles	7
Special feature 125°C "Euro 6" version Packaging without packaging No. of connected plugs 2 No. of connected sockets 0 Housing material reinforced composite Housing color black Contact insert color black Cable outlet molded Mounting of cable and socket/plug molded Working length [in m] 3.0 Max. working length [in m] 4.0 Max. extension length [in m] 4.5 Outer coil diameter [in mm] 50.0 Material of cable Cable color black PUR Cable color black Pire cross-sectional area 6x 1.5mm² + 1x 2.5mm² Protection IP 44 Temperature resistance [in °C] -40.0 - 125.0 Product supplement 125°C	Voltage [in V]	24
Packaging without packaging No. of connected plugs 2 No. of connected sockets 0 Housing material reinforced composite Housing color black Contact insert color black Cable outlet molded Mounting of cable and socket/plug molded Working length [in m] 3.0 Max. working length [in m] 4.0 Max. extension length [in m] 4.5 Outer coil diameter [in mm] 50.0 Material of cable PUR Cable color black Wire cross-sectional area 6x 1.5mm² + 1x 2.5mm² Protection IP 44 Temperature resistance [in °C] -40.0 - 125.0 Product supplement 125°C	Standard	ISO 1185 - Type N
No. of connected plugs 2 No. of connected sockets 0 Housing material reinforced composite Housing color black Contact insert color black Cable outlet molded Mounting of cable and socket/plug molded Working length [in m] 3.0 Max. working length [in m] 4.0 Max. extension length [in m] 4.5 Outer coil diameter [in mm] 50.0 Material of cable PUR Cable color black Wire cross-sectional area 6x 1.5mm² + 1x 2.5mm² Protection IP 44 Temperature resistance [in °C] -40.0 - 125.0 Product supplement 125°C	Special feature	125°C "Euro 6" version
No. of connected sockets 0 Housing material reinforced composite Housing color black Contact insert color black Cable outlet molded Mounting of cable and socket/plug molded Working length [in m] 3.0 Max. working length [in m] 4.0 Max. extension length [in m] 4.5 Outer coil diameter [in mm] 50.0 Material of cable PUR Cable color black Wire cross-sectional area 6x 1.5mm² + 1x 2.5mm² Protection IP 44 Temperature resistance [in °C] -40.0 - 125.0 Product supplement 125°C	Packaging	without packaging
Housing material reinforced composite Housing color black Contact insert color black Cable outlet molded Mounting of cable and socket/plug molded Working length [in m] 3.0 Max. working length [in m] 4.0 Max. extension length [in m] 4.5 Outer coil diameter [in mm] 50.0 Material of cable PUR Cable color black Wire cross-sectional area 6x 1.5mm² + 1x 2.5mm² Protection IP 44 Temperature resistance [in °C] -40.0 - 125.0 Product supplement 125°C	No. of connected plugs	2
Housing color black Contact insert color black Cable outlet molded Mounting of cable and socket/plug molded Working length [in m] 3.0 Max. working length [in m] 4.0 Max. extension length [in m] 4.5 Outer coil diameter [in mm] 50.0 Material of cable PUR Cable color black Wire cross-sectional area 6x 1.5mm² + 1x 2.5mm² Protection IP 44 Temperature resistance [in °C] -40.0 - 125.0 Product supplement 125°C	No. of connected sockets	0
Contact insert color black Cable outlet molded Mounting of cable and socket/plug molded Working length [in m] 3.0 Max. working length [in m] 4.0 Max. extension length [in m] 4.5 Outer coil diameter [in mm] 50.0 Material of cable PUR Cable color black Wire cross-sectional area 6x 1.5mm² + 1x 2.5mm² Protection IP 44 Temperature resistance [in °C] -40.0 - 125.0 Product supplement 125°C	Housing material	reinforced composite
Cable outlet molded Mounting of cable and socket/plug molded Working length [in m] 3.0 Max. working length [in m] 4.0 Max. extension length [in m] 4.5 Outer coil diameter [in mm] 50.0 Material of cable PUR Cable color black Wire cross-sectional area 6x 1.5mm² + 1x 2.5mm² Protection IP 44 Temperature resistance [in °C] -40.0 - 125.0 Product supplement 125°C	Housing color	black
Mounting of cable and socket/plug molded Working length [in m] 3.0 Max. working length [in m] 4.0 Max. extension length [in m] 4.5 Outer coil diameter [in mm] 50.0 Material of cable PUR Cable color black Wire cross-sectional area 6x 1.5mm² + 1x 2.5mm² Protection IP 44 Temperature resistance [in °C] -40.0 - 125.0 Product supplement 125°C	Contact insert color	black
Working length [in m] 3.0 Max. working length [in m] 4.0 Max. extension length [in m] 4.5 Outer coil diameter [in mm] 50.0 Material of cable PUR Cable color black Wire cross-sectional area 6x 1.5mm² + 1x 2.5mm² Protection IP 44 Temperature resistance [in °C] -40.0 - 125.0 Product supplement 125°C	Cable outlet	molded
Max. working length [in m] 4.0 Max. extension length [in m] 4.5 Outer coil diameter [in mm] 50.0 Material of cable PUR Cable color black Wire cross-sectional area 6x 1.5mm² + 1x 2.5mm² Protection IP 44 Temperature resistance [in °C] -40.0 - 125.0 Product supplement 125°C	Mounting of cable and socket/plug	molded
Max. extension length [in m] 4.5 Outer coil diameter [in mm] 50.0 Material of cable PUR Cable color black Wire cross-sectional area 6x 1.5mm² + 1x 2.5mm² Protection IP 44 Temperature resistance [in °C] -40.0 - 125.0 Product supplement 125°C	Working length [in m]	3.0
Outer coil diameter [in mm] 50.0 Material of cable PUR Cable color black Wire cross-sectional area 6x 1.5mm² + 1x 2.5mm² Protection IP 44 Temperature resistance [in °C] -40.0 - 125.0 Product supplement 125°C	Max. working length [in m]	4.0
Material of cable PUR Cable color black Wire cross-sectional area 6x 1.5mm² + 1x 2.5mm² Protection IP 44 Temperature resistance [in °C] -40.0 - 125.0 Product supplement 125°C	Max. extension length [in m]	4.5
Cable color black Wire cross-sectional area 6x 1.5mm² + 1x 2.5mm² Protection IP 44 Temperature resistance [in °C] -40.0 - 125.0 Product supplement 125°C	Outer coil diameter [in mm]	50.0
Wire cross-sectional area 6x 1.5mm² + 1x 2.5mm² Protection IP 44 Temperature resistance [in °C] -40.0 - 125.0 Product supplement 125°C	Material of cable	PUR
Protection IP 44 Temperature resistance [in °C] -40.0 - 125.0 Product supplement 125°C	Cable color	black
Temperature resistance [in °C] -40.0 - 125.0 Product supplement 125°C	Wire cross-sectional area	6x 1.5mm² + 1x 2.5mm²
Product supplement 125°C	Protection	IP 44
··	Temperature resistance [in °C]	-40.0 - 125.0
Brand Euro 6	Product supplement	125°C
	Brand	Euro 6



???Seite_Nummer??? 04/2024 www.erich-jaeger.com