


## **DATA**sheet

## 2P/24V(168A) plug (VG 96917)





Art.Nr.	251096
Part. No.	231090

No. of poles         2           Voltage [in V]         24           Rated current / permanent load [in A]         168.0           Peak current / short-term load [in A]         305.0           Standard         VG 96917           Special feature         with rubberized metal screw ring (black)           Design/Version         rubberized           Housing material         break-proof metal           Housing color         black           Contact insert color         black           Cable outlet         cap nut           Contact version         contact pin           Contact surface         silver (Ag)           Contact termination         solder contact, crimp contact           Contact: for max. wire cross section [in mm²]         50.0           Type of seal         sealing plug           No. of seal outlets         double           For cable diameter         13,00mm           13,00mm         13,00mm	Product group	Plug
Noltage [in V] 24  Rated current / permanent load [in A] 168.0  Peak current / short-term load [in A] 305.0  Standard VG 96917  Special feature with rubberized metal screw ring (black)  Design/Version rubberized  Housing material break-proof metal  Housing color black  Contact insert color black  Cable outlet cap nut  Contact version contact pin  Contact surface silver (Ag)  Contact termination solder contact, crimp contact  Contact: for max. wire cross section [in mm²] 50.0  Type of seal sealing plug  No. of seal outlets double  For cable diameter 13,00mm	Industry	Defense vehicles
Rated current / permanent load [in A] 168.0  Peak current / short-term load [in A] 305.0  Standard VG 96917  Special feature with rubberized metal screw ring (black)  Design/Version rubberized  Housing material break-proof metal  Housing color black  Contact insert color black  Cable outlet cap nut  Contact version contact pin  Contact surface silver (Ag)  Contact termination solder contact, crimp contact  Contact: for max. wire cross section [in mm²] 50.0  Type of seal sealing plug  No. of seal outlets double  For cable diameter 13,00mm	No. of poles	2
Peak current / short-term load [in A] 305.0  Standard VG 96917  Special feature with rubberized metal screw ring (black)  Design/Version rubberized  Housing material break-proof metal  Housing color black  Contact insert color black  Cable outlet cap nut  Contact version contact pin  Contact surface silver (Ag)  Contact termination solder contact, crimp contact  Contact: for max. wire cross section [in mm²] 50.0  Type of seal sealing plug  No. of seal outlets double  For cable diameter 13,00mm  13,00mm	Voltage [in V]	24
Standard VG 96917  Special feature with rubberized metal screw ring (black)  Design/Version rubberized  Housing material break-proof metal  Housing color black  Contact insert color black  Cable outlet cap nut  Contact version contact pin  Contact surface silver (Ag)  Contact termination solder contact, crimp contact  Contact: for max. wire cross section [in mm²] 50.0  Type of seal sealing plug  No. of seal outlets double  For cable diameter 13,00mm  13,00mm	Rated current / permanent load [in A]	168.0
Special feature with rubberized metal screw ring (black)  Design/Version rubberized  Housing material break-proof metal  Housing color black  Contact insert color black  Cable outlet cap nut  Contact version contact pin  Contact surface silver (Ag)  Contact termination solder contact, crimp contact  Contact: for max. wire cross section [in mm²] 50.0  Type of seal sealing plug  No. of seal outlets double  For cable diameter 13,00mm	Peak current / short-term load [in A]	305.0
Design/Version rubberized Housing material break-proof metal Housing color black Contact insert color black Cable outlet cap nut Contact version contact pin Contact surface silver (Ag) Contact termination solder contact, crimp contact Contact: for max. wire cross section [in mm²] 50.0 Type of seal sealing plug No. of seal outlets double For cable diameter 13,00mm 13,00mm	Standard	VG 96917
Housing material break-proof metal Housing color black  Contact insert color black  Cable outlet cap nut  Contact version contact pin  Contact surface silver (Ag)  Contact termination solder contact, crimp contact  Contact: for max. wire cross section [in mm²] 50.0  Type of seal sealing plug  No. of seal outlets double  For cable diameter 13,00mm  13,00mm	Special feature	with rubberized metal screw ring (black)
Housing color black  Contact insert color black  Cable outlet cap nut  Contact version contact pin  Contact surface silver (Ag)  Contact termination solder contact, crimp contact  Contact: for max. wire cross section [in mm²] 50.0  Type of seal sealing plug  No. of seal outlets double  For cable diameter 13,00mm  13,00mm	Design/Version	rubberized
Contact insert color black  Cable outlet cap nut  Contact version contact pin  Contact surface silver (Ag)  Contact termination solder contact, crimp contact  Contact: for max. wire cross section [in mm²] 50.0  Type of seal sealing plug  No. of seal outlets double  For cable diameter 13,00mm 13,00mm	Housing material	break-proof metal
Cable outlet cap nut  Contact version contact pin  Contact surface silver (Ag)  Contact termination solder contact, crimp contact  Contact: for max. wire cross section [in mm²] 50.0  Type of seal sealing plug  No. of seal outlets double  For cable diameter 13,00mm	Housing color	black
Contact version contact pin  Contact surface silver (Ag)  Contact termination solder contact, crimp contact  Contact: for max. wire cross section [in mm²] 50.0  Type of seal sealing plug  No. of seal outlets double  For cable diameter 13,00mm 13,00mm	Contact insert color	black
Contact surface silver (Ag)  Contact termination solder contact, crimp contact  Contact: for max. wire cross section [in mm²] 50.0  Type of seal sealing plug  No. of seal outlets double  For cable diameter 13,00mm	Cable outlet	cap nut
Contact termination solder contact, crimp contact  Contact: for max. wire cross section [in mm²] 50.0  Type of seal sealing plug  No. of seal outlets double  For cable diameter 13,00mm 13,00mm	Contact version	contact pin
Contact: for max. wire cross section [in mm²] 50.0  Type of seal sealing plug  No. of seal outlets double  For cable diameter 13,00mm 13,00mm	Contact surface	silver (Ag)
Type of seal sealing plug  No. of seal outlets double  For cable diameter 13,00mm  13,00mm	Contact termination	solder contact, crimp contact
No. of seal outlets double  For cable diameter 13,00mm 13,00mm	Contact: for max. wire cross section [in mm²]	50.0
For cable diameter 13,00mm 13,00mm	Type of seal	sealing plug
For cable diameter 13,00mm	No. of seal outlets	double
Protection IP X4,IP X7,IP 54	For cable diameter	
	Protection	IP X4,IP X7,IP 54



???Seite\_Nummer??? 04/2024 www.erich-jaeger.com