


DATAsheet

7P/12V 100% waterproof "JAEGER Expert" socket (SAE J560 - Primary)





Art.Nr.	101379
Part. No.	101379

No. of poles 7 Voltage [in V] 12 Standard SAE J560 - Primary Special feature unmounted Packaging PE bag Content of package contacts, contact insert, seal, cover cap Design/Version with reinforcement bushings Housing material reinforced composite Housing color black Cover material reinforced composite Cover color black Contact insert color green Cable outlet corrugated tube NW17, cable outlet 90° Contact version contact pin Contact surface nickel (Ni) Contact termination crimp contact Protection IP X9K,IP X7,IP 54 Temperature resistance [in °C] -40.0 - 85.0 Product supplement 100% waterproof	Product group	Socket	
Voltage [in V] 12 Standard SAE J560 - Primary Special feature unmounted Packaging PE bag Content of package contacts, contact insert, seal, cover cap Design/Version with reinforcement bushings Housing material reinforced composite Housing color black Cover material reinforced composite Cover color black Contact insert color green Cable outlet corrugated tube NW17, cable outlet 90° Contact version contact pin Contact surface nickel (Ni) Contact termination crimp contact Protection IP X9K,IP X7,IP 54 Temperature resistance [in °C] -40.0 - 85.0 Product supplement 100% waterproof	Industry	Commercial vehicles	
Standard SAE J560 - Primary Special feature unmounted Packaging PE bag Content of package contacts, contact insert, seal, cover cap Design/Version with reinforcement bushings Housing material reinforced composite Housing color black Cover material reinforced composite Cover color black Contact insert color green Cable outlet corrugated tube NW17, cable outlet 90° Contact version contact pin Contact surface nickel (Ni) Contact termination crimp contact Protection IP X9K,IP X7,IP 54 Temperature resistance [in °C] -40.0 - 85.0 Product supplement 100% waterproof	No. of poles	7	
Special feature unmounted Packaging PE bag Content of package contacts, contact insert, seal, cover cap Design/Version with reinforcement bushings Housing material reinforced composite Housing color black Cover material reinforced composite Cover color black Contact insert color green Cable outlet corrugated tube NW17, cable outlet 90° Contact version contact pin Contact surface nickel (Ni) Contact termination crimp contact Protection IP X9K,IP X7,IP 54 Temperature resistance [in °C] -40.0 - 85.0 Product supplement	Voltage [in V]	12	
Packaging PE bag Content of package contacts, contact insert, seal, cover cap Design/Version with reinforcement bushings Housing material reinforced composite Housing color black Cover material reinforced composite Cover color black Contact insert color green Cable outlet corrugated tube NW17, cable outlet 90° Contact version contact pin Contact surface nickel (Ni) Contact termination crimp contact Protection IP X9K,IP X7,IP 54 Temperature resistance [in °C] -40.0 - 85.0 Product supplement 100% waterproof	Standard	SAE J560 - Primary	
Content of package contacts, contact insert, seal, cover cap Design/Version with reinforcement bushings Housing material reinforced composite Housing color black Cover material reinforced composite Cover color black Contact insert color green Cable outlet corrugated tube NW17, cable outlet 90° Contact version contact pin Contact surface nickel (Ni) Contact termination crimp contact Protection IP X9K,IP X7,IP 54 Temperature resistance [in °C] -40.0 - 85.0 Product supplement 100% waterproof	Special feature	unmounted	
Design/Version with reinforcement bushings Housing material reinforced composite Housing color black Cover material reinforced composite Cover color black Contact insert color green Cable outlet corrugated tube NW17, cable outlet 90° Contact version contact pin Contact surface nickel (Ni) Contact termination crimp contact Protection IP X9K,IP X7,IP 54 Temperature resistance [in °C] -40.0 - 85.0 Product supplement 100% waterproof	Packaging	PE bag	
Housing material reinforced composite Housing color black Cover material reinforced composite Cover color black Contact insert color green Cable outlet corrugated tube NW17, cable outlet 90° Contact version contact pin Contact surface nickel (Ni) Contact termination crimp contact Protection IP X9K,IP X7,IP 54 Temperature resistance [in °C] -40.0 - 85.0 Product supplement 100% waterproof	Content of package	contacts, contact insert, seal, cover cap	
Housing color black Cover material reinforced composite Cover color black Contact insert color green Cable outlet corrugated tube NW17, cable outlet 90° Contact version contact pin Contact surface nickel (Ni) Contact termination crimp contact Protection IP X9K,IP X7,IP 54 Temperature resistance [in °C] -40.0 - 85.0 Product supplement 100% waterproof	Design/Version	with reinforcement bushings	
Cover material reinforced composite Cover color black Contact insert color green Cable outlet corrugated tube NW17, cable outlet 90° Contact version contact pin Contact surface nickel (Ni) Contact termination crimp contact Protection IP X9K,IP X7,IP 54 Temperature resistance [in °C] -40.0 - 85.0 Product supplement 100% waterproof	Housing material	reinforced composite	
Cover color black Contact insert color green Cable outlet corrugated tube NW17, cable outlet 90° Contact version contact pin Contact surface nickel (Ni) Contact termination crimp contact Protection IP X9K,IP X7,IP 54 Temperature resistance [in °C] -40.0 - 85.0 Product supplement 100% waterproof	Housing color	black	
Contact insert color green Cable outlet corrugated tube NW17, cable outlet 90° Contact version contact pin Contact surface nickel (Ni) Contact termination crimp contact Protection IP X9K,IP X7,IP 54 Temperature resistance [in °C] -40.0 - 85.0 Product supplement 100% waterproof	Cover material	reinforced composite	
Cable outlet corrugated tube NW17, cable outlet 90° Contact version contact pin Contact surface nickel (Ni) Contact termination crimp contact Protection IP X9K,IP X7,IP 54 Temperature resistance [in °C] -40.0 - 85.0 Product supplement 100% waterproof	Cover color	black	
Contact version contact pin Contact surface nickel (Ni) Contact termination crimp contact Protection IP X9K,IP X7,IP 54 Temperature resistance [in °C] -40.0 - 85.0 Product supplement 100% waterproof	Contact insert color	green	
Contact surface nickel (Ni) Contact termination crimp contact Protection IP X9K,IP X7,IP 54 Temperature resistance [in °C] -40.0 - 85.0 Product supplement 100% waterproof	Cable outlet	corrugated tube NW17, cable outlet 90°	
Contact termination crimp contact Protection IP X9K,IP X7,IP 54 Temperature resistance [in °C] -40.0 - 85.0 Product supplement 100% waterproof	Contact version	contact pin	
Protection IP X9K,IP X7,IP 54 Temperature resistance [in °C] -40.0 - 85.0 Product supplement 100% waterproof	Contact surface	nickel (Ni)	
Temperature resistance [in °C] -40.0 - 85.0 Product supplement 100% waterproof	Contact termination	crimp contact	
Product supplement 100% waterproof	Protection	IP X9K,IP X7,IP 54	
	Temperature resistance [in °C]	-40.0 - 85.0	
Brand JAEGER Expert	Product supplement	100% waterproof	
	Brand	JAEGER Expert	



???Seite_Nummer??? 04/2024 www.erich-jaeger.com